



OPERATORI PER CANCELLI A BATTENTE

OPERATORS FOR SWING GATES



Operatori a braccio

Arm operators

FOLDY_BB

CARATTERISTICHE PRINCIPALI

MAIN DETAILS

- Operatore a braccio elettromeccanico 230 Vac - Electromechanical arm operator 230 Vac
- Struttura in alluminio e carter in ABS - Aluminium structur and cover in ABS
- Braccio articolato anti-cesoiamento - Articulated arm anti-crushing
- Svincolo interno con maniglia - Internal device with handle



Prodotto Product	Descrizione Description
FOLDY/I4 (KBB003A00)	Operatore irreversibile . 4 poli 230 V per anta max. 2 m con finecorsa, carter in ABS, Arm operator selflocking 230 V for leaf max. 2 m with limitswitches, cover in ABS, External device with cable optional
FOLDY/R6 (KBB300A00)	Operatore reversibile 6 poli 230 V per anta max. 2,5 m con finecorsa carter in ABS, Svincolo interno con maniglia Reversible arm operator 230 V for leaf max. 2,5 m with limitswitches cover in ABS, External device with cable optional
LL366/KT	Kit tappi/angus piastra LL366F,F1 (IP55) Caps and angus kit for LL366F,F1 (IP55)

OPTIONALS (FOLDY_BB)

MC300/BAU	Braccio articolato unificato standard lenght
MC300/BB1	Braccio articolato standard destro - Articulated standard arm right Ad esaurimento/Out of stocks
MC300/BB2	Articulated standard arm left - Articulated standard arm left Ad esaurimento/Out of stocks
MC300/BAUL	Braccio articolato unificato special lenght
MC300/BB1L	Braccio articolato lungo DX - Long arm right Ad esaurimento/Out of stocks
MC300/BB2L	Braccio articolato lungo SX - Long arm left Ad esaurimento/Out of stocks
BL22/BTU	Braccio telescopico unificato - Telescopic arm
KBS000A00	Kit finecorsa ricambio da montare su operatore - Kit kimit switches SPARE to install on the operator
BB/BDC	Braccio dritto con cuscinetto - Right arm with bearing
BL22/BR/C	Guida per BB/BDC - Rail for BB/BDC
RID98/MS2 KBB003KF00	Kit svincolo esterno con cavo completo di - Kit external device with cable composed by: - Maniglia svincolo con chiave. - Handle for manual release - Kit fune svincolo 6 mtr. - Kit rope 6 mtr. For manual device
ENE512/K	Kit Encoder per FOLDY - Kit Encoder for FOLDY
LL378/K	kit manopola svincolo AF132F - handle AF132F manual release kit

ARMONY

CARATTERISTICHE PRINCIPALI

MAIN DETAILS

- Operatore a braccio elettromeccanico 24 Vac con finecorsa e fermi meccanici
- Electromechanical arm operator 24 Vac with limitswitch and mechanical stop
- Braccio articolato anti-cesoiamento - Articulated arm anti-crushing
- Svincolo interno con maniglia - Internal device with handle



	Prodotto Product	Descrizione Description	
	ARMONY	Operatore irreversibile . 24 V per anta max. 2 m con finecorsa, fermi meccanici, carter in ABS, Arm operator selflocking 24V for leaf max. 2 m with limitswitches,mechanical stop, cover in ABS, External device with cable optional	